

PRODUCT TECHNICAL SPECIFICATIONS

Nr. TP-311 REV. 0 DATE: 09-12-2021

PRODUCT:

MOBILE FIRE EXTINGUISHER OF 50 LITERS OF WATER

TYPE: EXTINGUISHER MOBILE WATER

CODE: FIEWM503

FEATURES:

Mobile fire extinguisher, permanently pressurized water with additives, rechargeable steel cylinder.

SKETCH:

REGULATIONS AND REGISTERS

Pressure Equipment Directive UE 2014/68/UE;

- -Pressure Equipment Regulations; -Regulation of fire protection facilities;
- -European standard UNE EN 1866; -European standard UNE-EN 615:
- **Extinguishing agents**
- Mark €€,
- Quality assurance according EN ISO 9001;
- Mark product quality,
- Quality magnag, system certificate.

| TECHNICAL SPECIFICATIONS | | | |
|--|-----------|--|--|
| Test pressure | 30 bar | | |
| Working pressure (to 20 °C) | 17,5 bar | | |
| Working pressure (to 60 °C) | 18,5 bar | | |
| Load (tolerance: +0-5%) | 50 liters | | |
| Fire rating (efficacy) | 34A IVB | | |
| Working temperatures | 5/60 C° | | |
| Propelling load (tolerance ± 10%) | 560 g | | |
| | | | |
| DIMENSIONS | | | |
| Height | 1097 mm | | |
| Diameter | 300 mm | | |
| Nominal thickness | 2,5 mm | | |
| Volume | 52 liters | | |
| Tare (cylinder, valve and syphon tube) | 30,36 kg | | |
| Total mass (filled weight) | 82,40 kg | | |

| Nr. | DESCRIPTION OF THE PART | MATERIALS | QUANT. |
|-----|-------------------------------------|---|--------|
| 1 | CYLINDER FI W501 (BOTTLE + CHASSIS) | Steel plate, with plastic covering inside,DC-04 | 1 |
| 2 | VALVE FI W501 | Brass, steel and rubber | 1 |
| 3 | GAUGE (ø37 mm) | Chrome-plated brass | 1 |
| 4 | SYPHON TUBE FI W500 | PVC | 1 |
| 5 | HOSE VALVE FI W501 | Rubber, textile, steel and polypropylene | 1 |
| 6 | LABEL FI W501 | Silkscreen or adhesive acetate | 1 |
| 7 | EXTINGUISHER MEDIA | ABC multipurpose dry powder | 50 I |
| 8 | PROPELLANT | Dry nitrogen (N ₂) | 560 g |
| 9 | CYLINDER SEAL FI W500 | Elastomer | 1 |
| 10 | WAGON WHEEL ø≥280 mm | Polypropylene and synthetic rubber | 2 |
| 10 | THIRD WHEEL WITH BRAKE FI W501 | Zinc plated steel and rubber | |

SAFETY:

Safety pln in drivin handle; Safety seal on safety pin.

OBSERVATIOS:

Sultable for: A and B (Also with presence of electrical tension 35000V); Painted 100% polyester powder polymerized in oven red color RAL 3000. Wall support included.

NEW FIRE ICE, S.L.U.

Polig. Ind. de Castellanos, parc. 302 37439 CASTELLANOS DE MORISCOS (Salamanca) ESPAÑA (SPAIN) TIf 34-923361557, Fax 34-923361394

PREPARED:

A. G. REDONDO

APPROBED:

J. CASTILLA C.

60 60